

SAFETY DATA SHEET

Waste Water Additive

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Waste Water Additive

Product no.

350010001

Unique formula identifier (UFI)

0X94-78J5-010G-H4SC

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Klosetvæske til kemiske toiletter

Use descriptors (REACH)

Sectors of use	Description
LCS "C"	Consumer uses: Private households (= general public = consumers)
LCS "PW"	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Product category	Description
PC35	Washing and Cleaning Products (including solvent based products)
Process category	Description
PROC 8a	Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities
PROC 19	Hand-mixing with intimate contact and only PPE available
PROC 28	Manual maintenance (cleaning and repair) of machinery
Environmental release category	Description
ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8b	Wide dispersive indoor use of reactive substances in open systems

Uses advised against

No special

1.3. Details of the supplier of the safety data sheet

Company and address

CAMP+NATURE

Stensgårdvej 1

5500 Middelfart

Denmark

+45 70 28 56 88

Contact person

Lena Mensel Dohlmann

E-mail

Imd@thansen.dk



Revision

30-12-2021

SDS Version

2.0

Date of previous version

2021-12-16 (1.0)

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Acute Tox. 4; H302, Harmful if swallowed.

Skin Corr. 1C; H314, Causes severe skin burns and eye damage.

Eye Dam. 1; H318, Causes serious eye damage.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

Harmful if swallowed. (H302)

Causes severe skin burns and eye damage. (H314)

Safety statement(s)

General

If medical advice is needed, have product container or label at hand. (P101)

Keep out of reach of children. (P102)

Prevention

Wear eye protection / face protection / protective gloves. (P280)

Response

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. (P303+P361+P353)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338)

Storage

Store locked up. (P405)

Disposal

Dispose of contents/container to an approved waste disposal plant. (P501)

Hazardous substances

kvaternære ammoniumforbindelser, benzyl-C12-16-alkyldimethyl, chlorider

2.3. Other hazards

Additional labelling

Not applicable

Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Product/substance Identifier	% w/w	Classification	Note
------------------------------	-------	----------------	------

Waste Water Additive Page 2 of 13



kvaternære ammoniumforbindelser, benzyl- C12-16-alkyldimethyl, chlorider	CAS No.: 68424-85-1 EC No.: 270-325-2 REACH: Index No.:	5-10%	Acute Tox. 3, H301 Acute Tox. 3, H311 Skin Corr. 1C, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=1)
propan-2-ol	CAS No.: 67-63-0 EC No.: 200-661-7 REACH: 01-2119457558- 25-XXXX Index No.: 603-117-00-0	5-10%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
isopentyl salicylate	CAS No.: 87-20-7 EC No.: 201-730-4 REACH: 01-2120113917- 55-XXXX Index No.:	<0.05%	Acute Tox. 4, H302 Aquatic Chronic 2, H411
4-(2,6,6-trimethylcyclohex-1-ene-1-yl)-but-3-ene-2-one	CAS No.: 14901-07-6 EC No.: 238-969-9 REACH: 01-2119937833- 30-XXXX Index No.:	<0.01%	Aquatic Chronic 2, H411
Benzoic,acid,2-hydroxy-,hexyl,ester	CAS No.: 6259-76-3 EC No.: 228-408-6 REACH: Index No.:	<0.0015%	Skin Sens. 1B, H317 Aquatic Chronic 1, H410 (M=1)
3,7-Dimethyloctan-3-ol	CAS No.: 78-69-3 EC No.: 201-133-9 REACH: 01-2119454788- 21-XXXX Index No.:	<0.0015%	Skin Irrit. 2, H315 Skin Sens. 1B, H317 Eye Irrit. 2, H319
hydrogen [4-[4-(diethylamino)-2',4'-disulphonatobenzhydrylidene]cyc	CAS No.: 129-17-9 EC No.: 204-934-1 REACH: Index No.:	<0.0015%	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available. Other information

[1] European occupational exposure limit

Waste Water Additive Page 3 of 13



SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact

Upon irritation of the eye: Remove contact lenses. Flush eyes with plenty of water or salt water (20-30°C) for at least 15 minutes and continue until irritation stops. Make sure you flush under the upper and lower eyelids. Seek medical assistance immediately and continue flushing during transport.

Ingestion

In the case of ingestion, contact a doctor immediately. If the person is conscious, give them water. DO NOT try to induce vomiting, unless this is recommended by a doctor. Hold head facing down to prevent vomit returning mouth and throat. Prevent shock by keeping the injured person warm and calm. Initiate immediate resuscitation if breathing stops. If unconscious, roll the injured person into recovery position. Call an ambulance.

Burns

Not applicable

4.2. Most important symptoms and effects, both acute and delayed

Tissue-damaging effects: This product contains substances with skin corrosive properties. Inhaled vapour or aerosols may produce adverse effects to lungs, -irritations and burns in the respiratory organs -as well as coughing. Dermal contact and contact with the eye cause irreversible effects.

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Not applicable

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO2).

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.



SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

6.3. Methods and material for containment and cleaning up

Use sand, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 on "Disposal considerations" in regard of handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid direct contact with the product.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers and store protected from moisture and light. Containers should be dated when opened and tested periodically for the presence of peroxides. Do not exceed storage time limits.

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material

Always store in containers of the same material as the original container.

Storage temperature

> 0°C

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

propan-2-ol

Long term exposure limit (8 hours) (ppm): 400

Long term exposure limit (8 hours) (mg/m³): 999

Short term exposure limit (15 minutes) (ppm): 500

Short term exposure limit (15 minutes) (mg/m³): 1250

diphenyl ether

Long term exposure limit (8 hours) (ppm): 1

Long term exposure limit (8 hours) (mg/m³): 7

Short term exposure limit (15 minutes) (ppm): 2

Short term exposure limit (15 minutes) (mg/m³): 14

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002. EH40/2005 Workplace exposure limits (Fourth Edition 2020).

DNEL

No data available

PNEC



No data available

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and -showers are clearly marked.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

Generally

Use only CE marked protective equipment.

Respiratory Equipment

Type	Class	Colour	Standards	
В	Class 1 (low capacity)	Gray		

Skin protection

Recommended	Type/Category	Standards
No special when used as intended	-	-

Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile - Discard immediately after use	0.2	> 240	EN374-2, EN374-3, EN388	

Eye protection

Туре	Standards

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

Blue

Odour / Odour threshold



Faint

рΗ

7

Density (g/cm³)

0.99

Kinematic viscosity

Testing not relevant or not possible due to nature of the product.

Particle characteristics

Does not apply to liquids.

Phase changes

Melting point/Freezing point (°C)

Testing not relevant or not possible due to nature of the product.

Softening point/range (waxes and pastes) (°C)

Does not apply to liquids.

Boiling point (°C)

100.00 °C

Vapour pressure

Testing not relevant or not possible due to nature of the product.

Relative vapour density

Testing not relevant or not possible due to nature of the product.

Decomposition temperature (°C)

Testing not relevant or not possible due to nature of the product.

Data on fire and explosion hazards

Flash point (°C)

Testing not relevant or not possible due to nature of the product.

Ignition (°C)

Testing not relevant or not possible due to nature of the product.

Auto flammability (°C)

Testing not relevant or not possible due to nature of the product.

Lower and upper explosion limit (% v/v)

Testing not relevant or not possible due to nature of the product.

Solubility

Solubility in water

Soluble

n-octanol/water coefficient

Testing not relevant or not possible due to nature of the product.

Solubility in fat (g/L)

Testing not relevant or not possible due to nature of the product.

9.2. Other information

Other physical and chemical parameters

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

No special

10.4. Conditions to avoid

No special

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.



SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity

Product/substance

Test method

kvaternære ammoniumforbindelser, benzyl-C12-16-alkyldimethyl, chlorider

Species

Rat Route of exposure Oral Test LD50 795 mg/kg · Result

Other information

Product/substance

kvaternære ammoniumforbindelser, benzyl-C12-16-alkyldimethyl, chlorider

Test method **Species**

Dermal Route of exposure Test LD50

Result > 5000 mg/kg ·

Other information

Product/substance

propan-2-ol

Test method

Rabbit Species Dermal Route of exposure LC50 Test

Result 12.800 mg/kg ·

Other information

Product/substance

propan-2-ol

Test method

Species Rat Route of exposure Inhalation LC50 Test 72,6 mg/l 4 h · Result

Other information

Product/substance

propan-2-ol

Test method

Species Rat Route of exposure Oral Test LD50 Result 5.280 mg/kg ·

Other information

Harmful if swallowed.

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Waste Water Additive

Based on available data, the classification criteria are not met.



Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

Tissue-damaging effects: This product contains substances with skin corrosive properties. Inhaled vapour or aerosols may produce adverse effects to lungs, -irritations and burns in the respiratory organs -as well as coughing. Dermal contact and contact with the eye cause irreversible effects.

Endocrine disrupting properties

No special

Other information

propan-2-ol has been classified by IARC as a group 3 carcinogen.

SECTION 12: Ecological information

12.1. Toxicity

Product/substance kvaternære ammoniumforbindelser, benzyl-C12-16-alkyldimethyl, chlorider

Test method

Species Daphnia

Compartment

Duration 48 hours
Test EC50
Result 0,016 mg/l·

Other information

Product/substance kvaternære ammoniumforbindelser, benzyl-C12-16-alkyldimethyl, chlorider

Test method

Species Algae

Compartment

 $\begin{array}{ll} \text{Duration} & 72 \text{ hours} \\ \text{Test} & \text{EC50} \\ \text{Result} & 0,025 \text{ mg/l} \cdot \end{array}$

Other information

Product/substance kvaternære ammoniumforbindelser, benzyl-C12-16-alkyldimethyl, chlorider

Test method

Species Fish

Compartment

Duration 96 hours
Test LC50
Result 0,85 mg/l·

Other information

Product/substance propan-2-ol

Test method

Waste Water Additive Page 9 of 13



Species Fish

Compartment

Duration 7 days
Test LC50
Result 9.640 mg/l·

Other information

Product/substance propan-2-ol

Test method

Species Daphnia

Compartment

Duration 48 hours
Test EC50
Result 13.299 mg/l \cdot

Other information

12.2. Persistence and degradability

Product/substance kvaternære ammoniumforbindelser, benzyl-C12-16-alkyldimethyl, chlorider

Biodegradable Yes

Test method OECD 301 D
Result > 60%

Product/substance propan-2-ol

Biodegradable Yes

Test method OECD 301 E Result 95%

12.3. Bioaccumulative potential

Product/substance kvaternære ammoniumforbindelser, benzyl-C12-16-alkyldimethyl, chlorider

Test method

Potential No

bioaccumulation

LogPow No data available BCF No data available

Other information

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Endocrine disrupting properties

No special

12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

HP 6 - Acute toxicity

HP 8 - Corrosive



Avoid discharge to lakes, streams, sewers, etc.

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

EWC code

Waste group H

Waste group H

Specific labelling

Not applicable

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

14.1. - 14.4.

This product is within scope of the regulations of transport of dangerous goods.

▼ ADR/RID

UN- or ID number	UN proper shipping name	Labels	Packing group	Tunnel restriction code
1760	CORROSIVE LIQUID, N.O.S. (kvaternære ammoniumforbindelser, benzyl-C12-16-alkyldimethyl, chlorider)	8	III	3 (E)

IMDG

UN- or ID number	UN proper shipping name	Labels	Packing group	EmS
1760	CORROSIVE LIQUID, N.O.S. (kvaternære ammoniumforbindelser, benzyl-C12-16-alkyldimethyl, chlorider)	8	III	F-A, S-B

MARINE POLLUTANT

No

IATA

UN- or ID number	UN proper shipping name	Labels	Packing group
1760	CORROSIVE LIQUID, N.O.S. (kvaternære ammoniumforbindelser, benzyl-C12-16-alkyldimethyl, chlorider)	8	Ш

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Restrictions for application

People under the age of 18 shall not be exposed to this product.

Demands for specific education

No specific requirements

SEVESO - Categories / dangerous substances

Waste Water Additive



Not applicable

Additional information

Tactile warning.

If this product is sold in retail, it must be delivered with child-resistant fastening.

Sources

The Management of Health and Safety at Work Regulations 1999

The Health and Safety at Work etc. Act 1974 Regulations 2013.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

CLP Regulation (EC) No 1272/2008, as retained and amended in UK law.

EC-Regulation 1907/2006 (REACH), as amended by UK REACH Regulations SI 2019/758

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H225, Highly flammable liquid and vapour.

H301, Toxic if swallowed.

H302, Harmful if swallowed.

H311, Toxic in contact with skin.

H314, Causes severe skin burns and eye damage.

H315, Causes skin irritation.

H317, May cause an allergic skin reaction.

H318, Causes serious eye damage.

H319, Causes serious eye irritation.

H336, May cause drowsiness or dizziness.

H400, Very toxic to aquatic life.

H410, Very toxic to aquatic life with long lasting effects.

H411, Toxic to aquatic life with long lasting effects.

The full text of identified uses as mentioned in section 1

LCS "C" = Consumer uses: Private households (= general public = consumers)

LCS "PW" = Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

PROC 8a = Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC 19 = Hand-mixing with intimate contact and only PPE available

PROC 28 = Manual maintenance (cleaning and repair) of machinery

PC35 = Washing and Cleaning Products (including solvent based products)

ERC8a = Wide dispersive indoor use of processing aids in open systems

ERC8b = Wide dispersive indoor use of reactive substances in open systems

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals



IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit.

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVCB = Complex hydrocarbon substance

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP)

The safety data sheet is validated by

RH

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en