



# Action Fluid Spray

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830  
Date of issue: 8-10-2018 Revision date: 8-10-2018 Version: 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : Action Fluid Spray  
Product code : PO.20.04  
Vaporizer : Aerosol  
Product group : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Intended for general public  
Main use category : Industrial use, Professional use  
Use of the substance/mixture : Solvent-based cleaner

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Putoline Oil  
Dollegoorweg 15  
7602 EC Almelo - Netherlands  
T 0031 (0)546 81 81 65  
[vib@putoline.com](mailto:vib@putoline.com)

#### 1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Cardiff Centre) Gwenwyn Ward, Llandough Hospital	Penarth CF64 2XX Cardiff	0344 892 0111	

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP] Mixtures/Substances: SDS EU 2015: According to Regulation (EU) 2015/830 (REACH Annex II)

Aerosol, Category 1 H222;H229  
Skin corrosion/irritation, Category 2 H315  
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336  
Aspiration hazard, Category 1 H304  
Hazardous to the aquatic environment — Chronic Hazard, Category 2 H411  
Full text of H statements : see section 16

#### Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes skin irritation. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS02

GHS07

GHS09

Signal word (CLP)

: Danger

Hazardous ingredients

: Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Hazard statements (CLP)

: H222 - Extremely flammable aerosol.  
H229 - Pressurised container: May burst if heated.  
H315 - Causes skin irritation.  
H336 - May cause drowsiness or dizziness.  
H411 - Toxic to aquatic life with long lasting effects.

# Action Fluid Spray

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Precautionary statements (CLP)	: P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P271 - Use only outdoors or in a well-ventilated area. P302+P352 - IF ON SKIN: Wash with plenty of water. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
--------------------------------	---

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	(CAS-No.) 64742-49-0 (EC-No.) 927-510-4 (EC Index-No.) 649-328-00-1 (REACH-no) 01-2119475515-33	25 - 50	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
butane (containing < 0,1% butadiene (203-450-8)) substance with national workplace exposure limit(s) (GB)	(CAS-No.) 106-97-8 (EC-No.) 203-448-7 (EC Index-No.) 601-004-00-0 (REACH-no) 01-2119474691-32	25 - 50	Flam. Gas 1, H220 Press. Gas (Comp.), H280
Propane substance with a Community workplace exposure limit	(CAS-No.) 74-98-6 (EC-No.) 200-827-9 (EC Index-No.) 601-003-00-5 (REACH-no) 01-2119486944-21	10 - 25	Flam. Gas 1, H220 Press. Gas (Comp.), H280
Distillates (petroleum), hydrotreated heavy paraffinic	(CAS-No.) 64742-54-7 (EC-No.) 265-157-1 (EC Index-No.) 649-467-00-8 (REACH-no) 01-2119484627-25	10 - 25	Asp. Tox. 1, H304

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after ingestion	: Risk of lung oedema.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Pressurised container: May burst if heated.

# Action Fluid Spray

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 6.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Mechanically recover the product.

Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

butane (containing < 0,1% butadiene (203-450-8)) (106-97-8)		
United Kingdom	Local name	Butane
United Kingdom	WEL TWA (mg/m³)	1450 mg/m³
United Kingdom	WEL TWA (ppm)	600 ppm
United Kingdom	WEL STEL (mg/m³)	1810 mg/m³
United Kingdom	WEL STEL (ppm)	750 ppm
United Kingdom	Remark (WEL)	Carc (Capable of causing cancer and/or heritable genetic damage, only applies if Butane contains more than 0.1% of buta-1,3-diene)
United Kingdom	Regulatory reference	EH40/2005 (Third edition, 2018). HSE

### Propane (74-98-6)

EU	IOELV TWA (ppm)	1000 ppm
----	-----------------	----------

### 8.2. Exposure controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### Hand protection:

Protective gloves

# Action Fluid Spray

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Nitrile rubber (NBR), Neoprene rubber (HNBR)	5 (> 240 minutes), 6 (> 480 minutes)	>=0,35		EN 374

### Eye protection:

Safety glasses

Type	Use	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166

### Skin and body protection:

Wear suitable protective clothing

### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

### Personal protective equipment symbol(s):



### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colorless to Amber.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: -44 °C
Flash point	: -97 °C
Auto-ignition temperature	: 365 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapour pressure	: 8300 hPa at 20 °C
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0,669 g/cm³ at 20 °C
Solubility	: Water: Insoluble / Slightly miscible
Log Pow	: No data available
Viscosity, kinematic	: < 20,5 mm²/s
Viscosity, dynamic	: No data available
Explosive properties	: Pressurised container: May burst if heated.
Oxidising properties	: No data available
Lower explosive limit (LEL)	: 0,6 vol %
Upper explosive limit (UEL)	: 10,9 vol %

### 9.2. Other information

VOC content	: 538,2 g/l
-------------	-------------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

# Action Fluid Spray

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

#### Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)

LD50 oral rat	> 5840 mg/kg [OECD 401]
LD50 dermal rat	2920 mg/kg [OECD 402]
LC50 inhalation rat (mg/l)	> 23300 mg/m <sup>3</sup> (4h) [OECD 403]

#### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LD50 oral rat	> 5000 mg/kg (OECD 420 method)
LD50 dermal rabbit	> 2000 mg/kg (OECD 402 method)
LC50 inhalation rat (mg/l)	> 5,53 mg/l/4h (mg/L air, aerosol) (OECD 403 method)

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Not classified

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

Aspiration hazard : May be fatal if swallowed and enters airways.

### Action Fluid Spray

Vaporizer	Aerosol
Viscosity, kinematic	< 20,5 mm <sup>2</sup> /s

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

Acute aquatic toxicity : Not classified

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

#### Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)

LC50 fish 1	> 13,4 mg/l 96h (Oncorhynchus mykiss) [OECD 203]
EC50 Daphnia 1	3 mg/l 48h (Daphnia) [OECD 202]
ErC50 (algae)	10 - 30 mg/l 72h (Pseudokirchneriella subcapitata) [OECD 201]
NOEC chronic fish	1,53 mg/l 28d (Oncorhynchus mykiss) [QSAR Petrotox]
NOEC chronic crustacea	1 mg/l 21d (Daphnia magna) [OECD 211]

#### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LC50 fish 1	> 100 mg/l (Pimephales promelas, 96h) (OECD 203 method)
-------------	---

# Action Fluid Spray

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

EC50 Daphnia 1	> 10000 mg/l (Gammarus pulex, 48h) (OECD 202 method)
EC50 Daphnia 2	> 10000 mg/l (Daphnia magna, 48h) (OECD 202 method)
NOEC (acute)	>= 100 mg/l (Pseudokirchnerella subcapitata, 72h) (OECD 201 method)
NOEC chronic fish	>= 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox, 14/28d)
NOEC chronic crustacea	10 mg/l (Daphnia magna, 21d) (OECD 211 method)

### 12.2. Persistence and degradability

#### Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)

Biodegradation	98 % (28d) [OECD 301F]
----------------	------------------------

#### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Biodegradation	31 % (28d) (OECD 301F method)
----------------	-------------------------------

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available






## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
1950	1950	1950	1950	1950
<b>14.2. UN proper shipping name</b>				
AEROSOLS (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics )	AEROSOLS (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics )	Aerosols, flammable (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics )	AEROSOLS (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics )	AEROSOLS (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics )
<b>Transport document description</b>				
UN 1950 AEROSOLS (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics ), 2.1, (D), ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics ), 2.1, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1950 Aerosols, flammable (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics ), 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics ), 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics ), 2.1, ENVIRONMENTALLY HAZARDOUS
<b>14.3. Transport hazard class(es)</b>				
2.1	2.1	2.1	2.1	2.1
				
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>				
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes

# Action Fluid Spray

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

No supplementary information available

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

#### Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

#### Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

#### Inland waterway transport

Classification code (ADN)	: 5F
Special provisions (ADN)	: 190, 327, 344, 625
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E0
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01, VE04
Number of blue cones/lights (ADN)	: 1

#### Rail transport

Classification code (RID)	: 5F
Special provisions (RID)	: 190, 327, 344, 625
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P207, LP200
Special packing provisions (RID)	: PP87, RR6, L2
Mixed packing provisions (RID)	: MP9
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W14
Special provisions for carriage - Loading, unloading and handling (RID)	: CW9, CW12
Colis express (express parcels) (RID)	: CE2
Hazard identification number (RID)	: 23

# Action Fluid Spray

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : 538,2 g/l

Directive 2012/18/EU (SEVESO III)

Seveso III Part I (Categories of dangerous substances)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
P3a FLAMMABLE AEROSOLS 'Flammable' aerosols Category 1 or 2, containing flammable gases Category 1 or 2 or flammable liquids Category 1	150	500
E2 Hazardous to the Aquatic Environment in Category Chronic 2	200	500

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Full text of H- and EUH-statements:	
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

SDS EU (REACH Annex II)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*