

QUIXX PAINT REPAIR PEN+

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Date of issue: 3/21/2018 Revision date: 3/21/2018 Version: 1.00



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : QUIXX PAINT REPAIR PEN+

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public

Main use category : Consumer use

Use of the substance/mixture : Varnish

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

E.V.I. GmbH

Hainbuchenring 4

82061 Neuried - Germany

T +49 (0)89 745062-0 - F +49 (0)89 745062-99

www.e-v-i.de

Informing department

Abt. F&E / Regulatory Affairs

Email competent person

sds@kft.de

1.4. Emergency telephone number

Emergency number : National Health Service (NHS)
24 hour national number consumer
England and Scotland: 111
Wales: 0845 46 47
Northern Ireland: call your local General Practitioner

Call 999 if there is a life-threatening incident.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2 H225

Serious eye damage/eye irritation, Category 2 H319

Specific target organ toxicity — Single exposure, Category 3, Narcosis H336

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Highly flammable liquid and vapour. May cause drowsiness or dizziness. Causes serious eye irritation.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02



GHS07

Signal word (CLP) : Danger

Hazardous ingredients : n-butyl acetate; acetone

Hazard statements (CLP) : H225 - Highly flammable liquid and vapour.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.

Precautionary statements (CLP) : P102 - Keep out of reach of children.

QUIXX PAINT REPAIR PEN+

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P271 - Use only outdoors or in a well-ventilated area.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 - Call a POISON CENTER, a doctor if you feel unwell.

P501 - Dispose of contents and container to a hazardous or special waste collection point.

Child-resistant fastening

: Not applicable

Tactile warning

: Applicable

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
n-butyl acetate	(CAS-No.) 123-86-4 (EC-No.) 204-658-1 (EC Index-No.) 607-025-00-1	25 - 50	Flam. Liq. 3, H226 STOT SE 3, H336
acetone	(CAS-No.) 67-64-1 (EC-No.) 200-662-2 (EC Index-No.) 606-001-00-8	20 - 25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

: Call a poison center or a doctor if you feel unwell.

First-aid measures after inhalation

: Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical advice.

First-aid measures after skin contact

: Rinse skin with water/shower. Take off immediately all contaminated clothing.

First-aid measures after eye contact

: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion

: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects

: May cause drowsiness or dizziness.

Symptoms/effects after eye contact

: Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

: Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media

: Strong water jet.

5.2. Special hazards arising from the substance or mixture

Fire hazard

: Highly flammable liquid and vapour.

Hazardous decomposition products in case of fire

: Toxic fumes may be released. Carbon dioxide. Carbon monoxide.

QUIXX PAINT REPAIR PEN+

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

5.3. Advice for firefighters

Firefighting instructions	: Protect container with water spray.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	: Do not allow run-off from fire fighting to enter drains or water courses. Disposal must be done according to official regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Remove all sources of ignition.
6.1.1. For non-emergency personnel	
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing mist, vapours. Avoid contact with skin and eyes.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid sub-soil penetration. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Take up liquid spill into absorbent material. Take up mechanically (sweeping, shovelling) and collect in suitable container for disposal.
Other information	: Disposal must be done according to official regulations.

6.4. Reference to other sections

Information for safe handling. See section 7. Concerning personal protective equipment to use, see section 8. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing mist, vapours. Avoid contact with skin and eyes.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Ground/bond container and receiving equipment.
Storage conditions	: Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Heat and ignition sources	: Keep away from heat and direct sunlight.
Information about storage in one common storage facility	: Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

n-butyl acetate (123-86-4)		
EU	Local name	n-butyl acetate
EU	Notes	(Ongoing)
EU	Regulatory reference	SCOEL Recommendations
United Kingdom	Local name	Butyl acetate
United Kingdom	WEL TWA (mg/m ³)	724 mg/m ³
United Kingdom	WEL TWA (ppm)	150 ppm
United Kingdom	WEL STEL (mg/m ³)	966 mg/m ³

QUIXX PAINT REPAIR PEN+

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

n-butyl acetate (123-86-4)		
United Kingdom	WEL STEL (ppm)	200 ppm
United Kingdom	Regulatory reference	EH40. HSE
acetone (67-64-1)		
EU	Local name	Acetone
EU	IOELV TWA (mg/m ³)	1210 mg/m ³
EU	IOELV TWA (ppm)	500 ppm
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
United Kingdom	Local name	Acetone
United Kingdom	WEL TWA (mg/m ³)	1210 mg/m ³
United Kingdom	WEL TWA (ppm)	500 ppm
United Kingdom	WEL STEL (mg/m ³)	3620 mg/m ³
United Kingdom	WEL STEL (ppm)	1500 ppm
United Kingdom	Regulatory reference	EH40. HSE

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Hand protection:

Not required for normal conditions of use. In case of repeated or prolonged contact wear gloves. EN 374. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Please follow the instructions related to the permeability and the penetration time provided by the manufacturer. Gloves must be replaced after each use and whenever signs of wear or perforation appear

Eye protection:

Not required for normal conditions of use. Wear closed safety glasses. EN 166

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. AX (P3). EN 143. . Breathing equipment is only to be used in order to handle the residual risk of short term jobs if all other risk minimizing measures have been carried out e.g. retention and/or local exhaust

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: clear.
Colour	: No data available
Odour	: Solvent.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: Not self-igniting
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: Vapours are heavier than air
Relative density	: No data available
Density	: 0.94 g/l

QUIXX PAINT REPAIR PEN+

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Solubility	: Water: Very slightly soluble
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Product is not explosive.
Oxidising properties	: No data available
Lower explosive limit (LEL)	: Not applicable
Upper explosive limit (UEL)	: Not applicable

9.2. Other information

VOC content	: 66.5 %
-------------	----------

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)
Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met)
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)

SECTION 12: Ecological information

12.1. Toxicity

Acute aquatic toxicity	: Not classified (Based on available data, the classification criteria are not met)
Chronic aquatic toxicity	: Not classified (Based on available data, the classification criteria are not met)

12.2. Persistence and degradability

QUIXX PAINT REPAIR PEN+

Persistence and degradability	The product has not been tested.
-------------------------------	----------------------------------

QUIXX PAINT REPAIR PEN+

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

n-butyl acetate (123-86-4)	
Persistence and degradability	Readily biodegradable.
Biodegradation	83 % (28d; (OECD 301D method))

acetone (67-64-1)	
Persistence and degradability	Readily biodegradable.
Biodegradation	90.9 % (28 d; (OECD 301B method))

12.3. Bioaccumulative potential

QUIXX PAINT REPAIR PEN+	
Bioaccumulative potential	The product has not been tested.

n-butyl acetate (123-86-4)	
Log Pow	2.3 (25 °C; (OECD 117 method))
Log Kow	1.8
Bioaccumulative potential	No additional information available.

acetone (67-64-1)	
Bioconcentration factor (BCF REACH)	3 (calculated value)
Log Pow	-0.23 Quantitative structure-activity relationship (QSAR)
Bioaccumulative potential	No additional information available.

12.4. Mobility in soil

QUIXX PAINT REPAIR PEN+	
Ecology - soil	The product has not been tested.

n-butyl acetate (123-86-4)	
Ecology - soil	No additional information available.

acetone (67-64-1)	
Surface tension	23.3 mN/m (20 °C)
Ecology - soil	No additional information available.

12.5. Results of PBT and vPvB assessment

QUIXX PAINT REPAIR PEN+	
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII	
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	

Component	
n-butyl acetate (123-86-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
acetone (67-64-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Disposal must be done according to official regulations. European waste catalogue. Do not dispose of with domestic waste. Do not discharge into drains or the environment.
Additional information	: Flammable vapours may accumulate in the container.

QUIXX PAINT REPAIR PEN+






Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

HP Code	: HP3 - "Flammable:" — flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C; — flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air; — flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction; — flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa; — water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities; — other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste. HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration. HP4 - "Irritant — skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.
---------	--

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
1263	1263	1263	1263	1263
14.2. UN proper shipping name				
PAINT (n-butyl acetate ; acetone)	PAINT (n-butyl acetate ; acetone)	Paint (n-butyl acetate ; acetone)	PAINT (n-butyl acetate ; acetone)	PAINT (n-butyl acetate ; acetone)
Transport document description				
UN 1263 PAINT (n-butyl acetate ; acetone), 3, II, (D/E)	UN 1263 PAINT (n-butyl acetate ; acetone), 3, II	UN 1263 Paint (n-butyl acetate ; acetone), 3, II	UN 1263 PAINT (n-butyl acetate ; acetone), 3, II	UN 1263 PAINT (n-butyl acetate ; acetone), 3, II
14.3. Transport hazard class(es)				
3	3	3	3	3
				
14.4. Packing group				
II	II	II	II	II
14.5. Environmental hazards				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available				

14.6. Special precautions for user

- Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 163, 367, 640D, 650
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E2
Transport category (ADR)	: 2
Hazard identification number (Kemler No.)	: 33
Orange plates	:



Tunnel restriction code (ADR)	: D/E
EAC code	: •3YE

QUIXX PAINT REPAIR PEN+

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

- Transport by sea

Special provisions (IMDG) : 163, 367
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E2
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E

- Air transport

PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y341
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 353
PCA max net quantity (IATA) : 5L
CAO max net quantity (IATA) : 60L
Special provisions (IATA) : A3, A72, A192

- Inland waterway transport

Classification code (ADN) : F1
Special provisions (ADN) : 163, 367, 640D, 650
Limited quantities (ADN) : 5 L
Excepted quantities (ADN) : E2

- Rail transport

Classification code (RID) : F1
Special provisions (RID) : 163, 367, 640D, 650
Limited quantities (RID) : 5L
Excepted quantities (RID) : E2
Transport category (RID) : 2
Hazard identification number (RID) : 33

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008	acetone
3(a) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F	QUIXX PAINT REPAIR PEN+ - n-butyl acetate - acetone
3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	QUIXX PAINT REPAIR PEN+ - acetone
40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	acetone

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : 66.5 %
Other information, restriction and prohibition regulations : Take note of Directive 94/33/EC on the protection of young people at work.
Directive 2012/18/EU (SEVESO III) : P5c FLAMMABLE LIQUIDS
Flammable liquids, Categories 2 or 3 not covered by P5a and P5b

QUIXX PAINT REPAIR PEN+

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
DPD	Dangerous Preparations Directive 1999/45/EC
DSD	Dangerous Substances Directive 67/548/EEC
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
TLM	Median Tolerance Limit
vPvB	Very Persistent and Very Bioaccumulative

Data sources : Information provided by the manufacturer. MSDS of the supplier.

Department issuing data specification sheet: : KFT Chemieservice GmbH
Im Leuschnerpark. 3 64347 Griesheim
Postfach 1451 64345 Griesheim
Germany

Phone: +49 6155-8981-400 Fax: +49 6155 8981-500
Safety Data Sheet Service: +49 6155 8981-522

Contact person : Dr. Sandra Burkhard

Full text of H- and EUH-statements:

Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Flam. Liq. 2	H225	Calculation method
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H336	Calculation method

QUIXX PAINT REPAIR PEN+

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

KFT SDS EU 11

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product